

Weepa Products Pty Ltd (ABN 52 011 011 457) PO Box 3325 SOUTH BRISBANE QLD 4101 Phone (07) 3844 3744 enquiries@weepa.com.au www.weepa.com.au

Technical Datasheet 50 mm Stainless Steel Weepa (20-555W)

Description

A fully stainless steel, prestige weep hole former suitable for 50mm high or 'Roman' brick masonry walls. Promotes excellent cavity ventilation, protects against entry of vermin and sparks and embers from bushfires and forms a neat and attractive weep hole.

Applications

Provide weep holes to NCC:2019 Building Code of Australia Clause 3.3.5.9, in the form of 50mm Stainless Steel Weepa (Product Code 20-SSSW) for Level BAL-LOW, BAL-A12.5, BAL-A19 BAL-A29, BAL-A40 and BAL-FZ construction in bushfire prone areas as defined in AS3959:2018, in perpends to external leaves of cavity walls in the course directly above damp proof courses, flashing and cavity fill, and at the bottom of infill cavity. Spacing: not to exceed 1200 mm. Note: Designs for damper climates and air conditioned buildings could consider closer spacing for greater airflow and drier cavities.

Technical Information	
Size	50 mm (H) x 10 mm (W) x 105 mm (D)
Body	316 Stainless Steel
Ember/Vermin Guard	316 Stainless Steel, Punched 1.8mm aperture
Bushfire Compliance	AS3959:2018 BAL-LOW, BAL-A12.5, BAL-A19,
	BAL-A29, BAL-A40, BAL-FZ when used in masonry
	construction
Product Code	20-SSSW