

Weepa Products Pty Ltd (ABN 52 011 011 457) PO Box 3325 SOUTH BRISBANE QLD 4101 Phone (07) 3844 3744 enquiries@weepa.com.au www.weepa.com.au

Technical Datasheet **70 mm Bushfire Weepa** (15-NABW)

Description

A weep hole former suitable for applications requiring a shortened weep hole in masonry walls. Promotes excellent cavity ventilation, protects against entry of vermin and sparks and embers from bushfires and forms a neat and attractive weep hole.

Applications

Provide weepholes to NCC:2019 Building Code of Australia Clause 3.3.5.9, in the form of 70 mm Bushfire Weepa (Product Code 15-NABW) for Level BAL-LOW, BAL-A12.5, BAL-A19 construction in bushfire prone areas as defined in AS3959:2018, in perpends to external leaves of cavity walls in the course directly above damp proof courses, flashing and cavity fill, and at the bottom of infill cavity. Spacing: not to exceed 1200 mm.

Note: Designs for damper climates and air conditioned buildings could consider closer spacing for greater airflow and drier cavities.

Technical Information	
Size	75mm (H) x 10mm (W) x 70mm (D)
Body	Polypropylene
Vermin Guard	PVC
Mesh	SS316 Stainless Steel, wire aperture 0.415mm wire
	diameter 0.22 mm
Bushfire Compliance	AS3959:2018 BAL-LOW, BAL-A12.5, BAL-A19 when
	used in masonry construction
Product Code	15-NABW