

Weepa Products Pty Ltd (ABN 52 011 011 457)

PO Box 3325 SOUTH BRISBANE QLD 4101

Phone (07) 3844 3744 Fax (07) 3844 9844

enquiries@weepa.com.au

www.weepa.com.au



High Performance Bushfire Weepa Specifications

Applications

Perpend to external leaves of cavity walls in the course directly above damp proof courses, flashing and cavity fill, and at the bottom of infill cavity. Spacing: Not to exceed 1200mm.

Note: Designs for damper climates and air conditioned buildings should consider closer spacing for greater airflow in order to dry cavities.

Sample Specifications

Provide weepholes to AS3700 clause 4.7.2, in the form of High Performance Bushfire Weepa (Product Code 11-HPBW) for Level BAL-LOW, BAL-12.5, BAL19, BAL-29, BAL-40 (delete four) construction in bushfire prone areas as defined in AS3959:2009; in perpend to external leaves of cavity walls in the course directly above damp proof courses, flashing and cavity fill, and at the bottom of infill cavity. Spacing: Not to exceed 1200mm.

Note: Designs for damper climates and air conditioned buildings should consider closer spacing for greater airflow to dry cavities.

Technical Information

Feature	Data
Size	75 mm (H) x 10 mm (W) x 105 mm (D)
Body	Polypropylene
Vermin Guard	PVC
Mesh	T304 Stainless Steel, wire aperture 0.415mm wire diameter 0.22mm
Bushfire Compliance	AS3959:2009 BALs 12.5, 19, 29, 40 and FZ (FZ requires 10m vegetation set back)
Product Code	11-HPBW