



Weepa Products Pty Ltd
(ABN 52 011 011 457)
PO Box 3325 SOUTH BRISBANE QLD 4101
Phone (07) 3844 3744
enquiries@weepa.com.au
www.weepa.com.au

Technical Datasheet

New Generation Bushfire Weepa (23-NGBW)

Description

A weep hole former suitable for masonry walls. Promotes excellent cavity ventilation, protects against entry of vermin and sparks and embers from bushfires and forms a neat and attractive weep hole.

Applications

Provide weep holes to NCC:2019 Building Code of Australia Clause 3.3.5.9, in the form of New Generation Bushfire Weepa (Product Code 23-NGBW) for Level BAL-LOW, BAL-A12.5, BAL-A19, BAL-A29 and BAL-A40 construction in bushfire prone areas as defined in AS3959:2018, in perpend to external leaves of cavity walls in the course directly above damp proof courses, flashing and cavity fill, and at the bottom of infill cavity. Spacing: not to exceed 1200 mm.

Note: Designs for damper climates and air conditioned buildings could consider closer spacing for greater airflow and drier cavities.

Technical Information

Size	75 mm (H) x 10 mm (W) x 105 mm (D)
Body	Polypropylene (PP)
Ember/Vermin Guard	316 Stainless Steel, punched 1.8 mm aperture
Bushfire Compliance	AS3959:2018 BAL-LOW, BAL-A12.5, BAL-A19, BAL-A29, BAL-A40 when used in masonry construction
Product Code	23-NGBW