

Weepa Products Pty Ltd (ABN 52 011 011 457) PO Box 3325 SOUTH BRISBANE QLD 4101 Phone (07) 3844 3744 enquiries@weepa.com.au www.weepa.com.au

Technical Datasheet Stainless Steel Weepa (19-TSSW)

Description

A fully stainless steel, prestige weep hole former suitable for masonry walls. Promotes excellent cavity ventilation, protects against entry of vermin and sparks and embers from bushfires and forms a neat and attractive weep hole.

Applications

Provide weep holes to National Construction Code (NCC) 2022 and associated Australian Standards including AS3700:2018 and AS4773.2:2015 for masonry buildings, in the form of Stainless Steel Weepa (Product Code 19-TSSW) for Level BAL-LOW, BAL-A12.5, BAL-A19 BAL-A29, BAL-A40 and BAL-FZ construction in bushfire prone areas as defined in AS3959:2018, in perpends to external leaves of cavity walls in the course directly above damp proof courses, flashing and cavity fill, and at the bottom of infill cavity. Spacing: not to exceed 1200 mm.

Note: Designs for damper climates and air conditioned buildings could consider closer spacing for greater airflow and drier cavities.

Technical Information	
Size	75 mm (H) x 10 mm (W) x 105 mm (D)
Body	316 Stainless Steel
Ember/Vermin Guard	316 Stainless Steel, Punched 1.8mm aperture
Bushfire Compliance	AS3959:2018 BAL-LOW, BAL-A12.5, BAL-A19,
	BAL-A29, BAL-A40, BAL-FZ when used in masonry
	construction
Product Code	19-TSSW